1300nm ELED Module

Features

- High coupled power
- Peak wavelength 1310 nm
- 3 dB bandwidth >40 nm
- Cut off frequency > 150 MHz
- Operating temperature range 0°C to 70°C
- Hermetically sealed TO package in pigtailed or receptacle housing with FC, ST or SC connector



Specifications (100mA forward current, 25 °C)

Parameter	Symbol	Min	Typical	Max	Units
Peak Wavelength	λ	1280	1310	1330	nm
Spectral width FWHM	Δλ	-	-	40	nm
Coupled power to 62.5 μm fiber	Po	-	400	-	μW
Coupled power to 50 μm fiber	Po	-	400	-	μW
Coupled power to 9 μm fiber	Po	200	-	-	μW
Forward voltage	V_F	-	-	2	V
Rise/fall time (10% to 90%)	tr/tf	-	-	3	ns
Cut off frequency (Iop=100 mA, 20mA p-p)	B	150	-	-	Mb/s

Absolute Maximum Ratings

Parameter	Symbol	Min.	Max.	Unit
Operating temperature	To	0	+70	°C
Storage temperature	T_{stg}	-40	+85	°C
Reverse voltage	V_R	-	2	V
Forward current	Iop	-	150	mA
Lead Soldering Temperature (10sec)	T_L	-	260	°C

Ordering Information



Pin Connections



Dimension

Pigtail Type



Receptacle Type

FC-PM





FC-BM





ST-BM





ST-PM





SC





Sugar Cube

Pin Connections

PIN No.	FUNCTION
1	ANODE
2	CATHODE
3	ANODE
4	ANODE

Dimension (ST Receptacle) Unit mm



Units:mm

1300nm ELED Module Power-Iop Curve